



TECHNICAL INFORMATION

OEST DIMO LS SAE 5W-30

High-performance easy flowing motor oil, low in ashes for Euro IV-Engines

Description

OEST DIMO LS SAE 5W-30 is a SHPD multi grade easy flowing Diesel engine oil for all-season and optimized oil supply on utility vehicles.

The special formula with low ash values and minimized content of so called catalyst-toxins (such as sulfur and phosphorus) allows the application in vehicles with exhaust after treatment (especially diesel particle filter systems).

Particularly OEST DIMO LS SAE 5W-30 suits for the new engine generation Euro IV (since 1.1.2005) and EURO V (from 1.9.2009), but can be use in past Euro III (and lower)-engines as well.

As all-season oil to use in induction- and turbo-charged engines also for extreme demands. The favourable deep temperature viscosity assures a quick oiling-though of the lubricating points and a starting and warming period of the engine that is low in friction and wear. The easy-flowing features assure that the engine runs low in friction with corresponding fuel savings.

Qualifications

ACEA E6, E7
API CI-4
MAN 3477, 3271-1
Volvo VDS-3, CNG
Renault Truck RXD, RGD
MTU Type 3.1
Deutz DQC III-05

Approvals

MB 228.51 (pending)

Special features

OEST DIMO LS SAE 5W-30 avoids engine damages due to thixotropy at outside temperature below -20°C and millage. Oest DIMO LS SAE 5W-30 is particularly recommended to be used on Mercedes transporter (Vito, Sprinter).