



TECHNICAL INFORMATION

OEST DIMO TURBO PLUS SAE 15W-40

Description:

Super HD-motor oil for all diesel engines, developed for highest demands for supercharged diesel engines with prolonged oil intervals.

OEST DIMO TURBO PLUS SAE 15W-40 is also suitable for Otto engines.

Qualifications

ACEA A3/B4, E7

API SL / CI-4

MB 229.1

MTU Type 2

CAT ECF-2, -1a

ZF TE-ML 07C

Deutz DQC II-05

Cummins 20071/72/76/77/78

Releases submitted:

VOLVO VDS-3

Renault RLD-2

MAN M 3275-1

MB 228.3

Chemical and physical data:

Colour	DIN ISO 2049		4,0
Density at 15 °C	DIN 51757	g/cm ³	0,885
Dyn. viscosity at – 20 °C	DIN 51377	mPas	< 7000
kin. Viscosity at 40 °C	DIN 51562 T.1	mm ² /s	110
at 100 °C			14,5
Flash point	DIN ISO 2592	°C	230
Pour point	DIN ISO 3016	°C	-33

The analysis data mentioned above are type values.

Application:

All-season oil for all kinds of diesel engines, turbo charger included. Prolonged oil change intervals according to the rules of the vehicle manufacturers.

Advantages:

Best wear protection, also under highest continuous stress. Protection against bore polishing on the cylinder liners. Higher cleanness of the motor and safety reserves for prolonged oil change intervals and more difficult operating conditions. Lower maintenance charges through prolonged oil change intervals.

Edition June 2010