Geschäftsbereich Schmierstoffe

Verwaltung: Bahnhofstraße 5 Werk: Wittlensweiler Straße 54 D-72250 Freudenstadt Postfach 720, D-72237 Freudenstadt Tel. +49 (0)74 41/539-508 Fax +49 (0)74 41/539-149 www.oest.de info.gom@oest.de



TECHNICAL INFORMATION

OEST Leichtlauföl GM-D2 SAE 5W-30

High-performance engine oil

Description:

OEST Leichtlauföl GM-D2 SAE 5W-30 is a fuel-saving easing flowing engine oil of highest quality class for modern passengers cars and vans, especially developed for Opel, Mercedez-Benz and BMW vehicles with exhaust aftertreatment and turbo charger.

Advantages:

Optimised cold start features, low oil consumption as well as lower emission, excellent wear protection also for longer oil change intervals, engine cleanness, prolongs the endurance of the particle filtre and the catalyzer.

Qualifications:

ACEA C3-08, A3/B4-07 API SM / CF GM Dexos 2 MB 229.51 BMW Longlife-04 VW 50200 / 50500 / 50501

Application:

OEST Leichtlauföl GM-D2 SAE 5W-30 corresponds to the current GM specifications which are stipulated for application for all passenger cars, off-road and light commercial vehicles from Opel, Saab and Chevrolet from the year 2010 onwards, for which are recommended 5W-30 dexos2 (with exception of Z 19 DTR and A 20 DTR).

Furthermore it is applicable for all kind of older vehicles for which GM-LL-A 025 or GM-LL-B 025 have been valid.

Edition April 2010