



TECHNICAL INFORMATION

OEST ETA HCS SAE 5W-40

Description:

High performance easy-running engine oil (SAE 5W-40) with HC base oil for all Otto and diesel engines in passenger cars and estate cars, with or without turbo chargers.

Advantages:

Good for cold starts, low fuel consumption, resistant to wear also during unfavourable operating conditions and to oil mud, treating the catalyser with care, stable in viscosity.

Qualifications:

ACEA A3/B4
API SM / CF
BMW Longlife 98
Mercedes Benz 229.3
VW 502.00 / 505.00
Porsche A 40
Renault RN 0700/0710

Chemical and physical analysis:

| | | | |
|---------------------------|--------------|--------------------|--------|
| Colour | DIN ISO 2049 | | 2,5 |
| Density at 15 °C | DIN 51757 | g/cm ³ | 0,855 |
| Dyn. viscosity at - 30 °C | DIN 51377 | mPas | 6.110 |
| Kin. viscosity at 40 °C | DIN 51562 | mm ² /s | 85 |
| | | | 14,3 |
| Viscosity index | DIN ISO 2909 | VI | 175 |
| Flash point | DIN ISO 2592 | °C | 220 |
| Pourpoint | DIN ISO 3016 | °C | < - 35 |

The analysis data mentioned above are type values.

Edition June 2010