Geschäftsbereich Schmierstoffe

Verwaltung: Bahnhofstraße 5 Werk: Wittlensweiler Straße 54 D-72250 Freudenstadt Postfach 720, D-72237 Freudenstadt Tel. +49 (0)74 41/539-508 Fax +49 (0)74 41/539-149 www.oest.de info.gom@oest.de



TECHNICAL INFORMATION

OEST Mehrzweckfett LT 190 EP

- High performance lubricating grease -

Description:

OEST Mehrzweckfett LT 190 EP is a multi-purpose grease manufactured from high quality raw materials with chemically reacting EP-additives. It is extremely resistant against heat, oxidation, water and high pressure load.

Chemical and physical data:

Operating temperature		°C	-30 +120
Base oil viscosity at 40 ℃	DIN 51562	mm²/s	110
Dropping point	DIN ISO 2176	℃	175
Worked penetration	DIN ISO 2137	0,1 mm	265/295
Class of consistency (NLGI)	DIN 51818		2
Soap base		Lithium 12 Hydroxi-stearat	
VKA welding power	DIN 51350 T.4	N	2.400
Name	DIN 51502		KP2 K-30

The analysis data mentioned above are type values.

Application:

High-quality multi-purpose grease for plain and rolling bearings as well as other greasing points on the automotive-, building- and industrial machinery sector also under high pressure or impact load and vibrations.

Edition January 2001