



TECHNICAL INFORMATION

OEST HYDRO FLUID SPEZIAL WB

Description:

Universal tractor oil (UTTO) for agricultural tractors with combined oil supply of gear and hydraulic system "wet brakes" included.

Important quality features are a high resistance against ageing as well as an excellent lubricity and resistance against wear.

Slip sticking and brake noise is avoided due to the adjusted rubbing behaviour.

Chemical and physical data:

Density at 15 °C	DIN 51757	g/cm ³	0,885
Kinematic viscosity at 40 °C	DIN 51562 T.1	mm ² /s	59,0
at 100 °C			9,4
Viscosity index	DIN ISO 2909	VI	141
Flash point COC	DIN ISO 2592	°C	220
Pour point	DIN ISO 3016	°C	-36

The analysis data mentioned above are type values.

OEST HYDRO FLUID SPEZIAL WB fulfils the requirements of the following specifications:

API GL 4	John Deere J 20 C/D
Allison C-4	Case MS 1206/1207/1209
Caterpillar TO-2	MF M 1135/1141/1143
ZF TE-ML 03E, 05E, 06E	FORD M2C 86 B/C, 134 D
	Renault RA 180 596

OEST HYDRO FLUID SPEZIAL WB can not be used as a motor oil.

Edition: October 2007