



## TECHNICAL INFORMATION

### OEST SUPER TRAKTOR OIL UNIVERSAL SAE 10W-40

#### Description:

High performance, universal oil for agricultural vehicles and machinery, that can be used as motor oil for diesel engines (with or without turbo charging), for Otto engines as well as hydraulic oil and gear oil. It is also suitable for wet brakes and for clutches from power take offs.

OEST SUPER TRAKTOR OIL UNIVERSAL SAE 10W-40 corresponds to:

<b>As motor oil</b>	API CG-4/SF ACEA E3 MB 227.1 / 228.1 (invalid)
<b>As gear oil</b>	API GL 4 Allison C-4 Caterpillar TO-2 ZF TE-ML 06A/B/C, 07B
<b>As hydraulic oil</b>	HLPD / HVLPD Denison HF-2
<b>As special tractor oil</b>	Massey Ferguson M 1139, 1144, 1145 John Deere JDM J 27, J20 C/D Ford New Holland M2C-41B, 86A, 134D, 159B/C Case MS 1118 / 1209 Fiat AF 87 Steyr 397 88001 International Harvester B6

#### Chemical and physical data:

Engine oil	SAE		10W-40
Hydraulic oil	ISO-VG		32 - 100
Gear oil	SAE		80W-90, 85W-90
Density at 15 °C	DIN 51757	g/cm <sup>3</sup>	0,870
Kinematic viscosity at 40 °C	DIN 51562 T.1	mm <sup>2</sup> /s	87
at 100 °C			14,3
Flash point COC	DIN ISO 2592	°C	> 220
Pour point	DIN ISO 3016	°C	-30

The analysis data mentioned above are type values.

Edition September 2011