



## TECHNICAL INFORMATION

### OEST ATF D III

#### Description

OEST ATF D III is a gear oil for automatic transmissions as well as for servo steerings, hydraulic clutches and hydraulic systems in passenger cars, lorries, buses and construction machines.

#### Characteristics

- excellent oxidation stability and flowing properties under cold temperatures
- good sealing compatibility and foaming properties
- excellent protection against wear and a wide temperature range
- suitable for hydro-steering and hydraulic systems
- protection against corrosion and rust
- exact friction property according to the specification of the manufacturer

#### Qualifications and specifications

Allison C-4  
 Ford Mercon  
 GM Dexron III H  
 MAN 339 Typ Z-1 / V-1  
 MB sheet 236.1 and 236.5  
 Voith 55.6335.xx (formerly G 607)  
 ZF TE-ML 02F, 04D, 14A, 17C

#### Chemical and physical data

Colour	DIN ISO 2049		red
Density at 15 °C	DIN 51757	g/cm <sup>3</sup>	0,860
Viscosity at 40 °C	DIN 51562 T.1	mm <sup>2</sup> /s	36,0
at 100 °C		mm <sup>2</sup> /s	8,0
viscosity index	DIN ISO 2909		200
flash point COC	DIN ISO 2592	°C	180
pour point	DIN ISO 3016	°C	< - 40

Edition September 2008